

Product Specifications

Marking Engine

Technology	Electrophotography	
Print Speed	8.5" x 11":	Up to 101 ipm
	11" x 17":	Up to 52 ipm
	12" x 18":	Up to 50 ipm
	13" x 19":	Up to 48 ipm
	13" x 30":	Up to 28 ipm
Paper Size	Standard:	3.9" x 5.8" to 13" x 19.2"
	Optional:	5.5" x 7.2" to 13" x 51.2"
Paper Capacity ¹	Standard:	Up to 1,100 Sheets
	Optional:	Up to 11,100 Sheets
Paper Weight	Standard:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Optional:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Envelopes: ²	No. 10, ISO-C5, DL, Monarch, 6" x 9", 9" x 12", 10" x 13"
Automatic	Paper Size:	Up to 13" x 51.2" ³
Duplexing	Paper Weight:	Up to 150 lb. Cover ⁴ (400 gsm)
Power Source	(2) Single-Phase 200 - 240 V, 50/60 Hz, 20 A	
Weight	904 lb.	
Dimensions	62.3" W x 34.3" D x 40.9" H	

Input Accessories

-		
Multi-Drawer Paper Deck-E1	Paper Capacity: ¹	Up to 5,000 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight	
	Top/Middle:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Bottom:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Power Source:	110 – 127 V, 60 Hz, 7 A
	Weight:	392 lb.
	Dimensions:	38" W x 31.5" D x 42.5" H
POD Deck	Paper Capacity: ¹	Up to 3,500 Sheets
Lite-C1	Paper Size:	5.5" x 5.8" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Power Source:	120 – 127 V, 60 Hz, 2.2 A
	Weight:	168 lb.
	Dimensions:	28.2" W x 27" D x 22.6" H
POD Deck	Paper Capacity ¹	
Lite XL-A2	Up to 13" x 19.2":	Up to 3,500 Sheets
	Up to 13" x 30":	Up to 1,000 Sheets
	Paper Size:	5.5" x 5.83" to 13" x 30"
	Paper Weight:	
	Up to 13" x 19.2":	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Up to 13" x 30":	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Source:	120 – 127 V, 60 Hz, 2.2 A
	Weight:	249 lb.
	Dimensions:	43.5" W x 27" D x 22.6" H

Input Accessories (Continued):

Stack Bypass-D1	Paper Capacity:	Up to 250 Sheets
	Paper Size:	3.9" x 5.83" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Weight:	3 lb.
	Dimensions:	18" W x 15.1" D x 2.9" H
Long Sheet	Paper Capacity:	Up to 1 Sheet
Feeding	Paper Size:	8.3" x 19.2" to 13" x 51.2"
and Catch Tray-B1	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Weight:	2 lb.
	Dimensions:	24.9" W x 56.1" D x 56.1" H
Duplex	Image Sensor:	CCD
Color Image	Scan Speed:	Up to 270 opm (Letter, 300 dpi)
Reader-P1	Document Size:	2.8" x 5.5" to 12" x 24.8"
	Resolution:	Up to 600 x 600 dpi, 256 Gradations
	Tray Capacity: ¹	Up 200 Sheets
	Weight:	51 lb.
	Dimensions:	25.7" W x 23.3" D x 8.6" H
Finishing A Sensing Unit-B1 ⁵	ccessories Tasks:	Front-to-Back Alignment, Color Accuracy Check, Cross Shade Adjustment,
Unit-B1 ²		
	DEE	Secondary Transfer Adjustment
	DFE:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 VI.0 or Later
	DFE: Paper Weight:	PRISMAsync print server V8.3 or Later;
		PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover
	Paper Weight:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Paper Weight: Paper Size:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2"
	Paper Weight: Paper Size: Power Supply:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A
•	Paper Weight: Paper Size: Power Supply: Weight:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper
•	Paper Weight: Paper Size: Power Supply: Weight: Dimensions:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H
•	Paper Weight: Paper Size: Power Supply: Weight: Dimensions: Paper Type:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper 14 lb. Bond to 150 lb. Cover
•	Paper Weight: Paper Size: Power Supply: Weight: Dimensions: Paper Type: Paper Weight:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
•	Paper Weight: Paper Size: Power Supply: Weight: Dimensions: Paper Type: Paper Weight: Paper Size:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 3.9" x 7.2" to 11.9" x 19.2"
•	Paper Weight: Paper Size: Power Supply: Weight: Dimensions: Paper Type: Paper Weight: Paper Size: Detection Size:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 3.9" x 7.2" to 11.9" x 19.2" 0.2 mm x 0.2 mm to 1.4 mm x 1.4 mm Up to 11.9"
Inspection Unit-A1 ⁵	Paper Weight: Paper Size: Power Supply: Weight: Dimensions: Paper Type: Paper Weight: Paper Size: Detection Size: Scanning Width:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 3.9" x 7.2" to 11.9" x 19.2" 0.2 mm x 0.2 mm to 1.4 mm x 1.4 mm Up to 11.9"
•	Paper Weight: Paper Size: Power Supply: Weight: Dimensions: Paper Type: Paper Type: Paper Weight: Paper Size: Detection Size: Scanning Width: Inspection Works Inspection	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 3.9" x 7.2" to 11.9" x 19.2" 0.2 mm x 0.2 mm to 1.4 mm x 1.4 mm Up to 11.9" tation
•	Paper Weight: Paper Size: Power Supply: Weight: Dimensions: Paper Type: Paper Type: Paper Weight: Paper Size: Detection Size: Scanning Width: Inspection Works Inspection Tool OS: Mode: Inspection	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 3.9" x 7.2" to 11.9" x 19.2" 0.2 mm x 0.2 mm to 1.4 mm x 1.4 mm Up to 11.9" tation Windows [®] 10 Pro Log Only Mode, Purge and Recovery Mode
•	Paper Weight: Paper Size: Power Supply: Weight: Dimensions: Paper Type: Paper Type: Paper Weight: Paper Size: Detection Size: Scanning Width: Inspection Works Inspection Tool OS: Mode: Inspection Location:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 3.9" x 7.2" to 11.9" x 19.2" 0.2 mm x 0.2 mm to 1.4 mm x 1.4 mm Up to 11.9" tation Windows [®] 10 Pro Log Only Mode, Purge and Recovery Mode Up to 64
•	Paper Weight: Paper Size: Power Supply: Weight: Dimensions: Paper Type: Paper Type: Paper Weight: Paper Size: Detection Size: Scanning Width: Inspection Works Inspection Tool OS: Mode: Inspection	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2" 100 – 240 V, 50/60 Hz, 2.5 A 222 lb. 20.3" W x 29.5" D x 48.3" H Plain Paper, Coated Paper 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) 3.9" x 7.2" to 11.9" x 19.2" 0.2 mm x 0.2 mm to 1.4 mm x 1.4 mm Up to 11.9" tation Windows [®] 10 Pro Log Only Mode, Purge and Recovery Mode Up to 64

Document	Tray Capacity ¹	
Insertion Unit-R1 ⁵	Upper Tray:	Up to 200 Sheets
Unit-RI ²	Lower Tray:	Up to 200 Sheets
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Paper Size:	7.2" x 7.2" to 13" x 19.2"
	Power Supply:	100 – 240 V, 50/60 Hz, 1.4 A
	Weight:	135 lb.
	Dimensions:	29.4" W x 31.2" D x 55.4" H
Multi	Paper Weight	
Function Professional	Punching:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
Puncher-C1 ⁵	Creasing:	110 lb. Text to 110 lb. Cover (157 gsm to 300 gsm)
	Paper Size	
	Punching:	12" x 18", 11" x 17", Letter, Legal, Letter-R, Statement
	Creasing:	Letter-R, 11" x 17", 12" x 18", 13" x 19"
	Die Set Patterns:	Loose-Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Color Coil 44-Hole, Crease
	Power Supply:	115 V, 60 Hz, 3.8 A
	Weight:	225 lb.
	Dimensions:	17.5" W x 31.3" D x 40.9" H
	Dimensions.	17.9 W X J1.9 D X 40.9 H
GBC	Bound Book Size: ¹	7 to 100 Sheets
eWire Pro ⁷	Paper Size:	Letter, 5.5" x 8.5", Tab Stock
	Paper Weight:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Wire Choices:	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
	Stack Capacity:	Up to 35 Books
	Power Supply:	115 V, 60 Hz, 2.8A
	Weight:	500 lb.
	Dimensions:	35.8" W x 31.3" D x 42.6" H
Perfect Binder-F1 ⁵	Finished Book Size:	5.4" x 8" to 8.5" x 11.7"
	Book Thickness: ¹	10 to 200 Sheets (Up to 0.98")
	Body Paper Weight:	14 lb. Bond to 43 lb. Bond (52 gsm to 163 gsm)
	Cover Paper Weight:	24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)
		l: 3-Side Cut/1-Side Cut/No Cut
	Trim Range	
	Top/Bottom:	0.26" to 1.6"
	Side:	0.26" to 1.95"
	Power Source:	208 V, 60 Hz, 3 A
	Weight:	679 lb.
	Dimensions:	36.3" W x 31.1" D x 51.2" H

 Weight:
 109 lb.

 Dimensions:
 9.8" W x 31.2" D x 40.9" H

Purge Unit:

Power Supply: Weight:

Auto Recovery: Yes (Purge and Recovery Mode Only)

High Capacity Stacker-J1 120 – 240 V, 50/60 Hz, 1.4 A

High	Stack Canacity ¹	Up to 6,000 Sheets	
Capacity	Top Tray		
Stacker-J1	Capacity: ¹	Up to 200 Sheets	
	Paper Size:	5.5" x 7.2" to 13" x 19.2"	
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)	
	Power Source:	100 – 240 V, 50/60 Hz, 2.5 A	
	Weight:	265 lb.	
	Dimensions:		
	Dimensions:	35.4" W x 29.3" D x 44.9" H	
Plockmatic	Stack Height		
Multi Purpose	Sheets < 25.6":	Lip to 11.8"	
Stacker ⁸	Sheets > 25.6":		
	Paper Size:	8.3" x 11" to 13" x 30"	
	Paper Weight:	100 lb. Text to 130 lb. Cover	
	Faper Weight.	(148 gsm to 350 gsm)	
	Power Source:	100 – 240 V, 50/60 Hz, 2 A	
	Weight:	168 lb.	
	Dimensions:	41.8" W x 35.4" D x 26.8" H	
	Dimensions:	41.0 W X JJ.4 U X ZU.O N	
Paper Folding	Double		
Unit-K1 ⁹	Parallel Fold:	Legal, Letter-R	
	C/Accordion Fold:	-	
	Z-Fold:	Letter-R, 11" x 17"	
	Paper Weight:	14 lb. Bond to 28 lb. Bond	
		(52 gsm to 105 gsm)	
	Power Source:	From Finisher	
	Weight:	157 lb.	
	Dimensions:	13.2" W x 31.2" D x 46.9" H	
Staple	Tray Capacity ¹		
Finisher-AF1/	Top Tray:	Up to 1,000 Sheets	
Booklet	Lower Tray:	Up to 4,000 Sheets	
Finisher-AF1	Paper Weight		
	Stacking:	14 lb. Bond to 150 lb. Cover	
	<u>_</u>	(52 gsm to 400 gsm)	
	Corner Stapling:	14 lb. Bond to 120 lb. Cover (52 gsm to 325 gsm)	
	Booklet-	14 lb. Bond to 110 lb. Cover	
	Making:	(52 gsm to 300 gsm)	
	Staple Positions:	Corner, Double-Side	
	Paper Size		
	Stapling:	7.2" x 8.3" to 11.7" x 17"	
		: 8.3" x 11" to 13" x 19.2"	
	Stapling Capacity	,1	
	Corner/		
	Double Side: ¹	Up to 100 Sheets	
		Up to 25 Sheets	
	V-Fold:	Up to 5 Sheets without Stitch	
	Power Source:	120 – 240 V, 50/60 Hz, 8 A	
	Weight		
	Staple Finisher:	287 lb	
	-		
	Booklet Finisher		

Long Sheet	Stack Capacity: 1	100 Sheets
Feeding and Catch Tray-D1 ⁹	Paper Size:	4" x 5.83" to 13" x 30"
Catch Iray-DI		
Long Sheet	Stack Capacity ¹	
Catch Tray XL-B1 ⁹	Up to 30":	Up to 300 Sheets
AL-DI	Up to 51.2":	Up to 10 Sheets
	Paper Size:	4" x 5.83" to 13" x 51.2"
Puncher Unit-BS1 ¹²	Paper Sizes 2-Hole:	Level Letter D. Custers Size
OUIL-DOL-	2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.7" x 17")
	3-Hole:	11" x 17", Letter, Executive-R,
		Custom Size (9.5" x 7.2" to 11.7" x 17")
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Punch Waste Capacity:	Up to 6,000 Sheets
	Power Supply:	From the Finisher
DFD Adapter and Finisher	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Bridge-B1 ⁹	Supported	Plockmatic BLM50/35
	Finishing:	SDD BLM300C
		Plockmatic Multi Purpose Stacker
	Requirements:	Staple/Booklet Finisher-AF1
	Weight:	168 lb.
	Dimensions:	35.8" W x 29.3" D x 46.9" H
Booklet	Margin Trimming	Frant adap Trim
Trimmer-G1 ⁹	Margin Trimming: Trim Amount:	2 mm to 28 mm
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	From the Finisher
	Weight:	392 lb.
	Dimensions:	82.5" W x 31.1" D x 41" H
Two-Knife	Margin Trimming:	Top and Bottom
Trimmer and	Trim Amount:	2 mm to 15 mm
Conveyor Set ¹⁰	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	120 V, 50/60 Hz, 2.5 A
	Weight:	320 lb.
	Dimensions:	21.1" W x 30.3" D x 41" H
	Differisions.	
SDD Square-Fold	Booklet Capacity: ¹	Up to 25 Sheets
Booklet-Maker ¹⁰	Booklet	
	Input Size:	5.5"x 8.27" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	154 lb.
	Dimensions:	43.3" W x 23.6" D x 44.9" H

Finishing Accessories (Continued):

SDD Square-Fold Booklet-Maker with Two-Knife Trim ¹⁰	Booklet Capacity: ¹	Up to 25 Sheets
	Booklet Input Size:	5.5"x 8.27" to 9.6" x 12.6"
	Booklet Output Size:	4.7" x 7.9" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Trim Amount:	2 mm to 35 mm
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	573 lb.
	Dimensions:	62.7" W x 27.6" D x 51.2" H
Plockmatic BLM50/35	Booklet Size: ¹	Up to 35/50 Sheets
	Paper Size:	8.1" x 10.8" to 12.6" x 18"
Professional Booklet-Maker ⁸	Paper Weight	
BOOKIET-IMAKELA	Uncoated:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Coated:	28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)
	Trim Amount	
	Face:11	1 mm to 25 mm
	Top/Bottom: ¹²	5 mm to 30 mm
	Paper Rotating: ¹²	8.1" x 10.9" to 9.1" x 12.7"
	Weight:	1,049 lb.
	Dimensions:	114.3" W x 33.8" D x 42.5" H

Print Servers

PRISMAsync Print Server ⁷	System Software:	Version 8
	CPU:	Intel [®] Core i7 4770S @ 3.1 GHz
	Memory:	16 GB
	Hard Drive:	1.5 TB
	OS:	Windows [®] 10
	Standard:	Scheduler, DocBox, G7 Calibration, Page Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple Queues, Remote Control
	Optional:	Advanced Imposition, DP Link
imagePRESS	Fiery System:	FS500 Pro
Server D3000	CPU:	Intel [®] Core i5-6500 3.2GHz up to 3.6GHz with Turbo
	Memory:	8 GB
	Hard Drive:	2 TB
	OS:	Windows [®] 10
	Standard:	Fiery [®] Hot Folders, Virtual Printers, Unity Display, Fiery JDF, Fiery Command WorkStation 6, Paper Catalog, Fiery Spot-On, Fiery Remote Scan, Media Librarian
	Optional:	Graphic Arts Pro Package, Fiery JobMaster, Color Profiler Suite, Fiery JobFlow, Operator Attention Light Removable HDD, Integrated Interface, and Stand-NX GL
¹ Based on 20 lb. Bon ² Envelope Attachme		⁷ Multi Function Professional Puncher-C1 required.

² Envelope Attachment Kit required. ³ POD Deck Lite-XL or Long Sheet Feed

and Catch Tray-B1 required.

- ⁴ Multi Drawer Paper Deck-E1 or
- POD Deck Lite-C1 required.
- ⁵ Staple/Booklet Finisher-AF1 or
- High Capacity Stacker-J1 required. ⁶ High Capacity Stacker-J1 required.

⁸ High Capacity Stacker-J1 or DFD Adapter

and Finisher Bridge-B1 required.

- ⁹ Staple/Booklet Finisher-AF1 required.
- ¹⁰ Booklet Trimmer-K1 required.
- ¹¹ Optional trimmer required.

¹² Optional rotator required.



As an ENERGY STAR® Partner, Canon U.S.A., Inc. qualified this model as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and imagePRESS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. PRISMA is a registered trademark of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. Some printer output images may be simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.





©2022 Canon U.S.A., Inc. All rights reserved.

0622R2-iPV1000SS-PDF-IH